

GRANTS

LIXIL HOUSING TECHNOLOGY


LIXIL Minimalistic Design

Window with only necessary element for functionality



Extreme simplicity gives distinctive appearance

LIXIL Double Barrier Drainage System




































FEATURES

Hassel Free Hardware














VERSATILITY








Concealed Screen System





SPECIFICATION

*Sound performance is tested according to JIS regulation. 25 dB reduction is based on JIS standard environmen Please consult with sound consultant for detail.

Performance	Wind Pressure Resistance Water Tightness Air Tightness Noise Insulation	ASTM E330 ASTM E330 ASTM E283 JIS (A4706 & A4702)	2000Pa 300Pa 10.7m³/hxm² 25dB*	
Product color	Anodized	Natural White		
		Natural Silver		
		Shine Grey		
	Autumn Brown			
		Natural Black		
	Powder coated	*Qualicoat class 1-2		
Glass thickness	SG (Laminate) IGU	5-12 (13.52) 18-29.5		

LINE UP

Single Window			MIX	
Sliding window 2 panels 4 panels	Sliding door 2 panels 3 panels 4 panels 6 panels	Casement window Friction stay Awing window without limit arm Fix	Corner FIX L Corner FIX R Swinging door No door closer	
			Mullion	Ventilation slot



SHOWROOM

Building D, Crystal Design Center (CDC)

Praditmanutham Road, Bangkok 10240, Thailand

Tel: + 66-2-102-2222 press 1

Fax: + 66-2-102-2040

Opening Hours 9:00 am - 7:00 pm

LIXIL (Thailand) Public Co., Ltd.

1/6 Moo 1, Phaholyothin Road K.M.32, 12120, Thailand

Tel: + 66-2-901-4455 Fax: + 66-2-901-4488

